


















**KNAUF**CEILING  
Solutions

## DATASHEET VARIOLINE Metal




- VARIOLINE Metal is a range of printed mineral ceilings that provides a perforated metal appearance
- Choice of 4 different perforations for design flexibility
- The laminated acoustic surface provides up to Class A sound absorption performance


- Available in a wide range of edge details to suit all design and installation needs
- Ideal for offices, foyers and retail spaces

Edge details		VARIOLINE Metal (Alpha)			VARIOLINE Metal (dB)	VARIOLINE Metal (Acoustic)	VARIOLINE Metal (HD)	
		Board	Tegular 24/90	Tegular 15/90	Vector	SL2	Finesse	
Thickness (mm)		19	19	19	24	19	19	
Dimensions (mm)		600 x 600 625 x 625 1200 x 600 1250 x 625	600 x 600 625 x 625 1200 x 600	600 x 600 1200 x 600	600 x 600 625 x 625 1200 x 600	On Request	600 x 600 625 x 625 1200 x 600 1250 x 625	
System		Exposed demountable - System C			Semi-concealed tiles, demountable - System C	Semi-concealed planks, demountable - System I.3 (Bandrastrer - System I.2 / Corridor - System F.2)	Concealed, demountable - System A.2 / A.3	
Weight		3.3 kg/m <sup>2</sup> (Board, Tegular 24/90, Tegular 15/90) 5.0 kg/m <sup>2</sup> (SL2) 5.2 kg/m <sup>2</sup> (Finesse) 8.6 kg/m <sup>2</sup> (Vector)						
Colour		White, with printed patterns Rg 1.0-3.0, Rg 2.5-5.5, Rg 1.5-2.8D, Qg 3.0-8.5						
Sound absorption		EN ISO 354 $\alpha_w = \mathbf{0.95}$ (Board, Tegular 24/90, Tegular 15/90) as per EN ISO 11654 - <b>Class A</b> $\alpha_w = \mathbf{0.65 (H)}$ (Vector, SL2) as per EN ISO 11654 - <b>Class C</b> $\alpha_w = \mathbf{0.90}$ (Finesse) as per EN ISO 11654 - <b>Class A</b>						
		Frequency f (Hz)	125	250	500	1000	2000	4000
		$\alpha_p$ Board, Tegular 24/90, Tegular 15/90	0.50	0.80	0.90	0.90	1.00	1.00
		$\alpha_p$ Vector	0.45	0.40	0.60	0.80	0.95	1.00
		$\alpha_p$ SL2	0.50	0.45	0.60	0.85	0.95	0.95
		$\alpha_p$ Finesse	0.50	0.70	0.80	0.90	1.00	1.00
		NRC = <b>0.90</b> (Board, Tegular 24/90, Tegular 15/90) as per ASTM C 423						
		NRC = <b>0.70</b> (Vector, SL2) as per ASTM C 423						
		NRC = <b>0.85</b> (Finesse) as per ASTM C 423						
Sound attenuation		$D_{n,f,w} = \mathbf{28 dB}$ (Board, Tegular 24/90, Tegular 15/90) as per EN ISO 717-1			$CAC = \mathbf{29 dB}$ (Board, Tegular 24/90, Tegular 15/90) as per ASTM E 413-10			
		$D_{n,f,w} = \mathbf{34 dB}$ (Finesse) as per EN ISO 717-1			$CAC = \mathbf{35 dB}$ (Finesse) as per ASTM E 413-10			
		$D_{n,f,w} = \mathbf{38 dB}$ (Vector) as per EN ISO 717-1			$CAC = \mathbf{39 dB}$ (Vector) as per ASTM E 413-10			
		$D_{n,f,w} = \mathbf{40 dB}$ (SL2) as per EN ISO 717-1						
Fire reaction		Euroclass <b>A2-s1, d0</b> as per EN 13501-1						
Thermal conductivity		$\lambda = \mathbf{0.040 W/mk}$ (Board, Tegular 24/90, Tegular 15/90) as per EN 12667						
		$\lambda = \mathbf{0.075 W/mk}$ (Vector) as per EN 12667						
		$\lambda = \mathbf{0.060 W/mk}$ (SL2, Finesse) as per EN 12667						
Air permeability		<b>PM1</b> ( $\leq 30 \text{ m}^3/\text{hm}^2$ ) as per DIN 18177						
Humidity resistance		<b>95% RH</b>						
Indoor air quality		 A+						


Rg 1.0-3.0




Rg 2.5-5.5



Rg 1.5-2.8D



Qg 3.0-8.5



Product availability may vary from country to country. Please contact your local sales representative.  
For further information and legal notice, please visit our website.